


FBX BARRIER



The popular, rapid-action torque motor automatic barrier.

- Boom length options 4m and 6m
- Raise and Lower Push button control
- Safety Autoclose Loop

BENEFITS & FEATURES

- 100% duty rating - designed for continuous and frequent use.
- Torque Motor Barriers are instantly reversible and motor is constantly energized providing security locking and protection against low temperatures and damp conditions.

OPERATING SPEED

- Operating Speed - 4m boom 3.5-7 seconds
- Operating Speed - 6m boom 7 seconds

OPTIONS

- Can be interfaced to any access control systems.

SAFETY

- Safety Autoclose Vehicle detector loops

CIVIL REQUIREMENTS

Barrier Foundation:

600mm²

D: 450mm

Fixed End Rest Foundation:

400mm²

D: 300mm

Barrier Cabinet Dimensions:

L: 380mm


W: 350mm

H: 1210mm

Note: Power and control wiring ducts to be incorporated into foundations

ELECTRICAL REQUIREMENTS *

- 6 amp, 3 wire, 230V, 50Hz, single phase supply



Applications: The popular FBX Automatic Barrier is installed around the world providing many sites entrances and car parks with traffic control

* This is subject to a risk assessment to ensure the automatic equipment complies to BS EN 12453

+44(0)1293 422800
sales@frontierpitts.com
www.frontierpitts.com



FPI.4EXPFBX/MAY16